



Proppa Industries Manufacturing

ACRYLIC

(Proppa Paints)

Description	ACRYLIC is a high-quality acrylic matt emulsion which is tough and flexible, of proven durability and offering excellent alkali resistance. It is recommended for the decoration and protection of wall and ceiling surfaces where a matt washable finish is required.
Pack Size	4L / 10L / 20L
Color Range	Color chart
Properties	Water thin-able styrene acrylic binders
Drying Time	Surface dry: 1-2 hrs./coat
Density	1.4 Kg/L
Coverage	Up to 14 m ² per liter on smooth sealed surface.
Application	Brush , Roller or Spray gun
Thinning	Thin with clean water 20-30%
Shelf Life	18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat
Preparation	After suitable preparation, new or bare areas should be primed using one coat of PROPPA SEALER PRIMER. Do not apply in cold or damp conditions. Ideally any dirt should be removed by lightly rubbing down with Fine Glass paper without using any water at all. Water used in any quantity tends to soak through a porous film in poor condition and may affect its adhesion particularly when heavily coated the need for a primer is dependent upon the quality and porosity of the surface. Generally speaking, if the surface is to be repainted with emulsion, direct application may normally be carried out without a primer but thinning the first coat down to enable practical application and affect a seal
Safety, Health & Environment Information	-Keep container tightly closed -Keep out of reach of children -In case of contact with eyes, rinse immediately with water and seek medical assistance -Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.