



# Proppa Industries Manufacturing

## OIL

(Proppa Paints Super)

|                    |  |
|--------------------|--|
| <b>Description</b> | <b>OIL PAINT</b> is an alkyd enamel based liquid gloss paints for interior and exterior. Have an excellent obliterating power and dries to a hard brilliant gloss a good durability. Suitable for use on plaster, masonry, wood and metal surfaces that have been previously primed and suitably prepared. It should be used in conjunction with PROPPA PRIMER for best results. |
| <b>Pack Size</b>   | 1L / 2.5L /4.5L  |
| <b>Color Range</b> | Color chart  |
| <b>Properties</b>  | Based on long oil modified alkyd resin. All colors possess satisfactory heat resistance  |
| <b>Drying Time</b> | Touch dry: 2-3 hrs. Hard dry: 4-6 hrs.<br>Recoating: recoat-able after 8 hours under normal conditions   |
| <b>Density</b>     | 1.08 Kg/L  |
| <b>Coverage</b>    | Up to 10-12 m2 per liter depending on the porosity of the surfaces   |
| <b>Application</b> | Brush , Roller or Spray gun  |
| <b>Thinning</b>    | Thin with white spirit 20-30%  |
| <b>Shelf Life</b>  | 18 months from the date of manufacturing (unopened).<br>Normal storage avoids frost & excessive heat   |
| <b>Preparation</b> | Surfaces should be clean, dry and free from grease. Remove loose or flaking materials. After suitable preparation and priming of the surface, apply one or two coats of preferred oxide colors as required, allowing 8 hours between coats. Do not apply in cold or damp conditions.   |

### Safety, Health & Environment Information

- Keep container tightly closed
- Keep out of reach of children
- In case of contact with eyes, rinse immediately with water and seek medical assistance
- Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.