



Proppa Industries Manufacturing

OIL

(Proppa Paints Ultra)

| | |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | OIL ULTRA is an alkyd enamel based liquid gloss paints for interior and exterior. Have an excellent obliterating power and dries to a hard brilliant gloss a good durability. Suitable for use on plaster, masonry, wood and metal surfaces that have been previously primed and suitably prepared. It should be used in conjunction with PROPPA SUPER PRIMER for best results. |
| Pack Size | 1L / 2.5L / 4.5L |
| Color Range | Color chart |
| Properties | Based on long oil modified alkyd resin. All colors possess satisfactory heat resistance |
| Drying Time | Surface dry: 1-2 hrs./coat Recoating: 2-3 hrs./coat under normal conditions |
| Density | 1.08 Kg/L |
| Coverage | Up to 12-14 m ² per liter |
| Application | Brush , Roller or Spray gun |
| Thinning | Thin with white spirit 10-20% |
| Shelf Life | 18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat |
| Preparation | Surfaces should be clean, dry and free from grease. Remove loose or flaking material- also. After suitable preparation, apply one coat of PROPPA SUPER PRIMER followed by one coat of PROPPA ULTRA OIL PAINT. Do not apply in cold or damp conditions |

Safety, Health & Environment Information

- Keep container tightly closed
- Keep out of reach of children
- In case of contact with eyes, rinse immediately with water and seek medical assistance
- Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.