



Proppa Industries Manufacturing

OIL

(Proppa Paints)

Description	OIL PAINT is an alkyd enamel based liquid gloss paints for interior and exterior. Have an excellent obliterating power and dries to a hard brilliant gloss a good durability. Suitable for use on plaster, masonry, wood and metal surfaces that have been previously primed and suitably prepared. It should be used in conjunction with PROPPA PRIMER for best results.
Pack Size	1L / 4.5L
Color Range	Color Chart
Properties	Based on long oil modified alkyd resin. All colors possess satisfactory heat resistance
Drying Time	Surface dry: 1-2 hrs./coat Recoating: 2-3 hrs./coat under normal conditions
Density	1.08 Kg/L
Coverage	Up to 10-12 m2 per liter
Application	Brush , Roller or Spray gun
Thinning	Thin with white spirit 10-20%
Shelf Life	18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat
Preparation	Surfaces should be clean, dry and free from grease. Remove loose or flaking material- also. After suitable preparation, apply one coat of PROPPA PRIMER followed by one coat of PROPPA OIL PAINT. Do not apply in cold or damp conditions

Safety, Health & Environment Information

- Keep container tightly closed
- Keep out of reach of children
- In case of contact with eyes, rinse immediately with water and seek medical assistance
- Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.