



Proppa Industries Manufacturing

SEALER WHITE

(Proppa Paints Super)

Description	SEALER WHITE a specially developed pigmented stabilizing for use on masonry substrates to seal porous surfaces and also to provide a sound base on dusty or chalking areas before over-painting.
Pack Size	4L / 10L / 20L
Color Range	White
Properties	Based on alkali resistant copolymer resin.
Drying Time	Touch dry: 1 hour Hard dry: 3 hours Recoating 4 hour under normal conditions
Density	1.5 Kg/L
Coverage	Up to 12 m2 per liter depending on the porosity of the surfaces
Application	Brush, Roller or Spray gun
Thinning	Thin with clean water 20-30%
Shelf Life	18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat
Preparation	After suitable preparation. Do not apply in cold or damp conditions. Ideally any dirt should be removed by lightly rubbing down with Fine Glass paper without using any water at all. Water used in any quantity tends to soak through a porous film in poor condition and may affect its adhesion particularly when heavily coated the need for a primer is dependent upon the quality and porosity of the surface. Generally speaking, if the surface is to be repainted with emulsion, direct application may normally be carried out with PROPPA SEALER WHITE first coat down to enable practical application and affect a seal.
Safety, Health & Environment Information	<div><ul style="list-style-type: none">-Keep container tightly closed-Keep out of reach of children-In case of contact with eyes, rinse immediately with water and seek medical assistance-Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.</div>