



# Proppa Industries Manufacturing

## VARNISH

(Proppa Paints Super)

<b>Description</b>	<b>VARNISH</b> is a clear gloss finishes for interior and exterior use on natural wood. It combines a very high gloss with good durability. It is also recommended as high-quality pale varnish for use over oil paint, and for all good class exterior work, such as sign boards.
<b>Pack Size</b>	2.5L /4.5L
<b>Color Range</b>	Clear
<b>Properties</b>	Based on long oil alkyd, it has a flash point above 32C
<b>Drying Time</b>	Touch dry: 2-3 hrs. Hard dry: 4-6 hrs Recoating: recoat-able after 8 hours under normal conditions
<b>Coverage</b>	Up to 14 m2 per US gallon depending on the porosity of the surfaces
<b>Application</b>	Brush , Roller or Spray gun
<b>Thinning</b>	Thin with white spirit 20-30%
<b>Shelf Life</b>	18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat
<b>Preparation</b>	Surfaces should be clean, dry and free from grease. Remove loose or flaking materials. After suitable preparation such as teak, iroko or keruing should be washed down with polyurethane. When thinned apply two coats interior surfaces, and exterior surfaces apply three coats, lightly rubbing down with fine glass paper allowing 8 hours between coats. On exterior surfaces ensure that backs, sides and grains of the timber are fully protected. Do not apply in cold or damp conditions.
<b>Safety, Health &amp; Environment Information</b>	<div><ul style="list-style-type: none"><li>-Keep container tightly closed</li><li>-Keep out of reach of children</li><li>-In case of contact with eyes, rinse immediately with water and seek medical assistance</li><li>-Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.</li></ul></div>