



Proppa Industries Manufacturing

PROPPA GRAVIATO TEXTURE

(Proppa Paints Super)

Description	<p>PROPPA GRAFIATO TEXTURE Is an interior and exterior resin bonded plaster suitable for either new or previously painted cementitious substrate. Can also be applied on Brick Masonry, Gypsum Board and previously Painted Walls. It is uniquely formulated with exceptionally graded aggregates, extenders, inert pigments, special additives and a novel Pure Acrylic emulsion to provide superb weather-ability and texture. It incorporates versatile fungicides and algacides to combat mold and algae growth both in the wet and dry film state. It is an eco-friendly, water based with low VOC Level. Product is made to order with the exception of a few colors that are readily available.</p>						
Surface Preperation	<p>New Walls</p> <ul style="list-style-type: none">-Any loose materials, grease or dirt must be completely removed.-PROPPA GRAFIATO PRIMER must be applied before texturing. <p>Previously Painted Walls</p> <ul style="list-style-type: none">-Any deteriorated coats of old paint should be removed completely by scraping and wire brushing.-Any large cracks must be filled with PROPPA JOINT FLEX, and once dry then start with PROPPA GRAFIATO PRIMER to apply PROPPA GRAFIATO TEXTURE.						
Thinning & Mixing	<p>ready to use. DO NOT THIN.</p>						
Application Criteria	<ul style="list-style-type: none">-Application should not be carried out during adverse climatic conditions. Applied surfaces must be protected from direct sunlight and rain for 24 hours after application.-To be applied with masonry trowel and finished with a plastic/polystyrene float giving the desired texture.-For large sites that require scaffold use, the scaffold should be positioned at a comfortable distance away from the wall in order not to compromise the application technique.-Always use masking tape for joints to create paneling thus avoiding dry joints for large area application.-Stoppage during applications should be limited to ONLY 12 hours after the last application. This to avoid differential curing process, besides environmental effects on already applied coatings that shows variations in color and the texture finish.-The responsibility of color consistency is with the contractor. Sufficient material to complete the project should be ordered where possible to eliminate possible color variation. If not so, sufficient material to complete an elevation should be ordered.						
Application Method	<ul style="list-style-type: none">-On a fairly smooth surfaces, apply PROPPA GRAFIATO PRIMER then PROPPA GRAFIATO TEXTURE using steel float.-Always work in a VERTICAL upwards motion with one hand holding the STEEL FLOAT while the other hand flat SMOOTH PLASTIC FLOAT to collect any falling materials. This procedure will generate SHUDDER MARKS -i.e., wavy streaks caused by grits in the texture.-Now work from LEFT to RIGHT using a STEEL FLOAT to remove the shudder marks and excess material while allowing the GRITS/AGGREGATES heads to just POKE out of the surface of the applied texture.-ALWAYS stand perpendicular (in front) to the surface being worked to ensure GROOVES are running symmetrically to each other.						
Equipment Cleaning	<p>Clean the masonry trowel with water immediately after use.</p>						
Drying Time	<table><tr><td>Touch dry:</td><td>4 hours</td></tr><tr><td>Through dry:</td><td>24 hours</td></tr><tr><td>Hard dry:</td><td>7 days</td></tr></table>	Touch dry:	4 hours	Through dry:	24 hours	Hard dry:	7 days
Touch dry:	4 hours						
Through dry:	24 hours						
Hard dry:	7 days						
Safety, Health & Environment Information	<div><ul style="list-style-type: none">-Keep container tightly closed-Keep out of reach of children-In case of contact with eyes, rinse immediately with water and seek medical assistance-Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.</div>						