



Proppa Industries Manufacturing

PROPPA CHARM

(Proppa Paints Super)

Description	PROPPA CHARM latex emulsion is a good quality used on interior walls gyps, trim masonry surfaces. It merges slightly with P.O.P CEMENT POWDER for wall skimming for excellent finishes.
Pack Size	4L / 10L / 20L
Color Range	White
Properties	Water borne paint based on an emulsion resin Solid By weight 59% Solid By volume 39%
Drying Time	Surface dry: 1 hour Recoating: 2-3 hours Dry to handle: 2-3 hours “Depending on weather conditions”
Density	1.6 Kg/L
Coverage	Is dependent on various conditions like the preparatory of the surface, and the method of application in addition to the weather conditions, etc.
Application	New or bare surface must be clean, dry, and free from masonry salts. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper or stiff brush and dust off. Treat any area affected by mold, lichens, algae, or moss with bleach. Fill the surface with PROPPA CHARM P.O.P.
Thinning	1KG of P.O.P powder, 1L of distilled water, 2KG of PROPPA CHARM MIX WELL BEFORE USE
Shelf Life	18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat
Preparation	Allows all new surfaces to dry out completely. Remove all loose or defective paint or powdery residues by thorough brushing and scraping using a stiff fiber brush. Where appropriate, the surface should be rubbed down using a suitable abrasive paper and dusted off.
Safety, Health & Environment Information	<div><ul style="list-style-type: none">-Keep container tightly closed-Keep out of reach of children-In case of contact with eyes, rinse immediately with water and seek medical assistance-Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.</div>