

**Proppa Industries Manufacturing** 

## **READY MIX PUTTY FILLER**

(Proppa Paints)

- **Description READY MIX PUTTY FILLER** is an economical ready to use filler that has an excellent coverage and application properties. Its high-quality filling properties has made it ideal for use on all types of interior masonry surfaces. It provides a smooth base for all application of all decorative products.
- **Pack Size** 4L / 10L / 20L

Color Range White

- Properties Pigment: lightfast Non lead pigments Binder: PVA-Polymer Solvent: water
- **Drying Time** Surface dry: 1 hour Recoating: 2-3 hours Dry to handle: 2-3 hours "Depending on weather conditions"
- Thickness Wet: 200-250 micrometers Dry: 90-110 micrometers
- **Coverage** It depends on many factors like surface condition, surface preparation, application skill, weather conditions, etc.
- Application Knife, Roller
- Thinning Ready to use.
- Shelf Life18 months from the date of manufacturing (unopened). Normal storage<br/>avoids frost & excessive heat
- **Preparation** Allow all new surfaces to dry out completely. Remove all loose or defective paint or powdery residues by thorough brushing and scraping using a stiff fiber brush. Where appropriate, the surface should be rubbed down using a suitable abrasive paper and dusted off. New or bare surface must be clean, dry and free from masonry salts. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper or stiff brush and dust off. Treat any area affected by mold, lichens, algae or moss with bleach. Fill the surface with it. Allow it to dry and apply second coat. Third coat is recommended for extra smoothness. After drying scuff surface using abrasive paper and dust off.

Safety, Health	-Keep container tightly closed
& Environment	-Keep out of reach of children
Information	-In case of contact with eyes, rinse immediately with water and seek medical assistance
	-Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.