



Proppa Industries Manufacturing

EMULSION

(Proppa Paints)

Description

EMULSION This high opacity matt emulsion paint is specially formulated for contract work in interior wall or ceiling surfaces. It is ideally suited for use on new plaster, allowing the surface to breathe and dry out properly, whilst providing good obliteration at an economical price.

Pack Size

4L / 10L / 20L

Color Range

White, Light colors

Properties

Water borne paint based on an emulsion resin
Solid By weight 59%
Solid By volume 39%

Drying Time

Water borne paint based on copolymer binder resin
Surface dry: 1-2 hrs/coat
Recoating: 2-3 hrs/coat
under normal conditions

Density

1.6 Kg/L

Coverage

Up to 12 m² per liter

Application

Brush , Roller or Spray gun

Thinning

Thin with clean water 20-30%

Shelf Life

18 months from the date of manufacturing (**unopened**). Normal storage avoids frost & excessive heat

Preparation

After suitable preparation, new or bare areas should be primed using one coat of PROPPA SEALER. Do not apply in cold or damp conditions. Ideally any dirt should be removed by lightly rubbing down with Fine Glass paper without using any water at all. Water used in any quantity tends to soak through a porous film in poor condition and may affect its adhesion particularly when heavily coated the need for a primer is dependent upon the quality and porosity of the surface

Safety, Health & Environment Information

- Keep container tightly closed
- Keep out of reach of children
- In case of contact with eyes, rinse immediately with water and seek medical assistance
- Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.